

Contents

<i>Preface</i>	vii
1. Introduction	1
2. Joint Source-Channel Coding: An Overview	5
2.1 System Model	5
2.1.1 Channel	6
2.1.2 Encoder	7
2.1.3 Decoder	7
2.2 System Distortion	7
2.3 Optimal Decoder for a Given Encoder	9
2.4 Optimal Encoder	9
2.5 Special Cases	11
2.5.1 Preliminary Remarks	11
2.5.2 Gaussian Source and Gaussian Channel	11
2.5.3 Channels with Binary Input: Channel-Optimized Vector Quantization	14
2.6 Practical Approaches to Source-Channel Coding	24
2.6.1 Systems for Multimedia Transmission	24
2.6.2 Separation of Source and Channel Coding	25
2.6.3 Approaches to Joint Source-Channel Decoding	30
2.6.4 Approaches to Joint Source-Channel Encoding	34
3. Joint Source-Channel Decoding	37
3.1 Introduction and System Model	37
3.2 Near Optimum Joint Source-Channel Decoding	40

3.2.1	Specialization and Generalization	45
3.3	Iterative Source-Channel Decoding (ISCD)	46
3.3.1	Principle and Derivation	46
3.3.2	Efficient Implementation of ISCD by L-values	49
3.3.3	Simulation Results for ISCD	51
3.4	Quantizer Bit Mappings for ISCD	55
3.4.1	Basic Considerations	55
3.4.2	Optimization by Binary Switching	58
3.4.3	Simulation Results with Optimized Bit Mappings	61
3.5	Conclusions	65
4.	Channel-Adaptive Scaled Vector Quantization	67
4.1	Introduction	67
4.2	Memory and Complexity Issues for Vector Quantization (VQ) and Channel-Optimized VQ	68
4.3	Channel-Adaptive Scaled Vector Quantization	72
4.3.1	Basic Principle	72
4.3.2	Optimization of CASVQ	74
4.3.3	Complexity and Memory Requirements of CASVQ for Transmission over Time-Varying Channels	76
4.4	Simulation Results	78
4.5	Conclusions	82
5.	Index Assignments for Multiple Descriptions	85
5.1	Introduction	85
5.2	System Model	87
5.3	Optimal Decoder for a Given Index Assignment	88
5.4	Quality Criterion for the Index Assignments	90
5.5	Optimization of the Index Assignments	92
5.5.1	The Complexity Problem	92
5.5.2	Index Optimization by the Binary Switching Algorithm for a System with a Single Description	92
5.5.3	Binary Switching for Multiple Descriptions	93
5.6	Simulation Results	94
5.7	Conclusions	97
6.	Source-Adaptive Modulation	99
6.1	Introduction	99

6.2	Conventional System Model	100
6.2.1	Conventional Hard-Decision Receiver	102
6.2.2	Conventional Soft-Decision Receiver	103
6.3	Principle of Source-Adaptive Modulation (SAM)	104
6.4	SAM for Detection of M-PSK Signal Sets	106
6.4.1	Derivation of the Optimal Solution	106
6.4.2	Test-Point Method	113
6.4.3	Analytical Approximation	114
6.4.4	Simulation Results	116
6.5	SAM for Quadrature Amplitude Modulation	122
6.5.1	Discussion of Potential Signal-Point Locations	122
6.5.2	Simulation Results for SAM with QAM	126
6.6	Conclusions	128
7.	Source-Adaptive Power Allocation	129
7.1	Introduction	129
7.2	System Model	130
7.3	Principle of Source-Adaptive Power Allocation	131
7.4	Conventional Soft-Decision Receiver	135
7.5	Simulation Results	135
7.6	Conclusions	137
8.	Concluding Remarks	139
Appendix A	Theoretical Performance Limits	141
A.1	Preliminary Remarks	141
A.2	Important Distortion-Rate Functions	142
A.2.1	Memoryless Sources	142
A.2.2	Comparison with Practical Quantization Schemes	145
A.2.3	Gaussian Sources with Memory	148
A.3	Capacities of Practically Important Channels	153
A.3.1	Binary Symmetric Channel (BSC)	153
A.3.2	Binary Erasure Channel (BEC)	155
A.3.3	Additive White Gaussian Noise (AWGN) Channel	155
A.4	Performance Limits for the Transmission of Sources with Continuous-Values over Noisy Channels	168
A.4.1	Gaussian Source/AWGN Channel and BSC	169

A.4.2	Correlated Gaussian Source/AWGN Channel with Binary Input	170
A.4.3	Gaussian Source/Two-Dimensional AWGN Channel with PSK Input	172
Appendix B	Optimal Decoder for a Given Encoder	175
Appendix C	Symbol Error Probabilities for M-PSK	177
Appendix D	Derivative of the Expected Distortion for SAM	179
	<i>List of Symbols</i>	181
	<i>List of Acronyms</i>	185
	<i>Bibliography</i>	187
	<i>Index</i>	193